

Pressure Wash Hose



A096 YELLOW FLEX WASH DOWN HOSE



NRP Part Number	Hose I.D. (in.)	Hose O.D. (in.)	Max. W.P.	Min. Bend Radius	Wt. Per Foot (lbs.)
A096-06	3/8	0.69	3,000	5.0	.19
A096-08	1/2	0.82	3,000	7.0	.26
A096-12	3/4	1.10	2,000	9.5	.35

Application: Applications requiring resistance to animal fats such as poultry processing, meat packing, hotel, restaurant, agriculture and industrial maintenance. Both tube and cover FDA approved. Also, non-marking cover excellent for car wash applications. Recommended for service requiring resistance to petroleum based products.

NOT RECOMMENDED FOR STEAM SERVICE.

Tube: Black, special polymer compounded for heat and detergent resistance. Resistant to petroleum based products.

Reinforcement: One braid high tensile steel wire with open pattern for extra flexibility and resistance to mechanical damage.

Cover: Yellow, special polymer compounded for resistance to animal fat, detergent, abrasion and weathering.

Temperature: -40 to 300° F.

Fittings: NRP A096 Hose uses the same fittings as those for SAE 100R1AT.

Branding: YELLOW FLEX WASH DOWN HOSE 3000 PSI WP MADE IN USA.

Lengths: Random lengths on reels or cut to specification.

Premium Feature: Abrasion, age and ozone resistant. Heat resistant, easy identification, economical.

A098 BLUE PRESSURE WASHER HOSE

NRP Part Number	Hose I.D. (in.)	Hose O.D. (in.)	Max. W.P.	Min. Bend Radius	Wt. Per Foot (lbs.)
A098-04	1/4	.53	3,000	4.0	.17
A098-06	3/8	.69	3,000	5.0	.24
A098-08	1/2	.82	3,000	7.0	.28

Application: Extra high pressure hot water cleaning systems (portable and fixed installation units) in general use in agriculture, restaurant, hotel and industrial maintenance. This hose can also be used for service requiring resistance to petroleum based products or detergents.

NOT RECOMMENDED FOR STEAM SERVICE.

Tube: Black, oil resistant nitrile (NBR).

Reinforcement: One braid High Tensile Steel Wire.

Cover: Blue oil and abrasion resistant NBR/PVC.

Temperature: -45 to 300° F.

Fittings: NRP A098 hose uses same fittings as those for SAE 100R1AT.

Branding: NRP A098 PRESSURE WASH 3000 PSI WP MADE IN USA.

Lengths: Random lengths on reels or cut to specification.

Premium Feature: Abrasion, age and ozone resistant. Heat resistant, easy identification, economical.

A184 DUAL-LITE PRESSURE WASHER/HYDRAULIC HOSE

NRP Part Number	Hose I.D. (in.)	Hose O.D. (in.)	Max. PSI	Min. Bend Radius	Wt. Per Foot (lbs.)
A184-04	1/4	.53	3,000	4.0	.17
A184-06	3/8	.69	3,000	5.0	.24
A184-08	1/2	.82	3,000	7.0	.28

Application: Portable or fixed extra high pressure hot water cleaning systems for commercial and industrial maintenance. Also, hydraulic oil line applications which exceed SAE 100R1 temperature ratings and working pressures.

NOT RECOMMENDED FOR STEAM SERVICE.

Tube: Black, oil and high temperature resistant Nitrile (NBR).

Reinforcement: One braid of high tensile steel wire. The design burst is a 4 to 1 ratio of the maximum rated working pressure.

Cover: Black, oil and abrasion resistant NBR/PVC blend.

Temperature: Hot Water Pressure Systems -40 to +300° F. Hydraulic systems -40 to +300° F intermittent; or +250° F continuous.

Fittings: NRP A184 Hose uses the same fittings as those for SAE 100R1AT.

Branding: NRP A184 DUAL-LITE PRESSURE WASHER EXCEEDS SAE 100R1 3000 PSI WP MADE IN USA.

Lengths: Random lengths on reels or cut to specification.

Premium Feature: Dual purpose- Hydraulic systems and pressure washer. Heat resistant; abrasion, age and ozone resistant.